

ONELIGHT SPECTRA VISX PRODUCT SPECIFICATIONS

PRODUCT DESCRIPTION

ANY SPECTRUM
ANY INTENSITY
ANY TIME

ONELIGHT



Prerequisites

Standard Hardware

Standard Software

OneLight® Spectra VisX is a wide range spectrally programmable light engine that responds to your imaging needs from 380-720nm. It can provide any desired mix of wavelengths and can control the intensity at each wavelength independently. With the ability to respond faster than most imaging systems, OneLight Spectra can improve the performance of research as well as test and measurement. Using thousands of built-in and user-defined spectral profiles, OneLight Spectra eliminates the need for many costly light sources and filters; reducing the cost of components, eliminating repeated calibrations, improving time to market and time to publication for test results.

- ✓ New! **EXPANDED WIDER RANGE** of the original Spectra Visible.

The OneLight Spectra provides high-speed software control of output spectrum, intensity, exposure time and timing sequences. Output to existing equipment is highly configurable via liquid light guide connection compatible with many optical adapters. The application software allows users to control the instrument functions via a computer equipped with a standard USB 2.0 interface and high speed synchronization to other equipment via opto-isolated TTL I/O. A software Application Programming Interface (API) can be used to program custom applications. Spectra can be created and loaded on the fly based on response from image sensors.

- Instantaneous dynamic control of color, exposure and intensity
- Increased dynamic range of measurement
- Increased measurement sensitivity
- Built-in optical feedback capability
- Elimination of repeated calibrations
- Sequential loading of multiple spectra
- Easy connectivity to existing equipment (opto-isolated TTL I/O)
- Manufactured in ISO 9001:2000, AS9100B facility - FDA registered for medical devices

Windows XP or higher (32-bit mode only)

OneLight Spectra Light Engine (uses highly reliable 100,000 hour MTBF Texas Instruments DLP chip), power cord and USB cable.

SpectraGen Control software (includes automatic calibration)

[Video demo's at www.youtube.com/onelightcorp]

Documentation Included

OPTIONAL ACCESSORIES

Equipment

Software

PERFORMANCE

Output Intensity

Spectral Resolution

Spectral Range Options

Spectral Accuracy

Intensity Control Levels

Stray Light (Contrast)

Spectrum Rate

Exposure Time

Modulation Frequency

Operating Conditions

Electrical Requirements

Equipment Dimensions

Equipment Weight

Regulatory Compliance

OneLight Spectra Installation & User Guide, Factory calibration with wavelength calibration and output intensity profile

Feedback spectrometer (needed for calibration or feedback control, if desired), replacement lamp cartridge, light guide, power meter, microscope adapters (see Accessories data sheet for details).

Software Development Kit (SDK)

LabVIEW SDK and Drivers

Functional Source Code Examples (sequencing, tuner, all functions, calibration)

350 mW full spectrum; 1 mW/nm typical, 1.5 mW/nm peak

(at output of 5mm light guide, 14 nm resolution)

14 nm standard (Slit A); 21 nm optional (Slit B)

Antireflection coated for 380 – 720 nm

(Actual range depends on choice of diffraction grating and other options)

1 nm

Greater than 65,000 (in a 10nm band), Flicker < 1%

0.0012, (850 : 1)

Up to 7,000 spectra/second from computer (up to 3000 with no pre-loading)

Programmable to 140µs

Up to 3.5 kHz

Temperature 5-35°C Relative Humidity 20%-90%

100-240 VAC, 50/60Hz, 700W

D43 x W24 x H39 cm (add 5cm to D for light guide connector nosepiece)

17 kg/ 37 lbs

CE Marked & Certified to EN 55011:2001, EN 61326-1:2006

Note- all specifications are believed to be accurate at time of printing, but specifications are subject to change as a result of design modifications or additional information

OneLight Spectra VISX Output

